

**No. SJ25-95
SINGLE JACKET 250 PSI MILL HOSE**



Part Number	Inside Diameter	Standard Length	Test Pressure -PSI	Service Pressure-PSI
SJ25-95-1550	1-1/2"	50'	250	125
SJ25-95-1566	1-1/2"	66'	250	125
SJ25-95-15100	1-1/2"	100'	250	125
SJ25-95-2050	2"	50'	250	125
SJ25-95-2066	2"	66'	250	125
SJ25-95-20100	2"	100'	250	125
SJ25-95-2550	2-1/2"	50'	250	125
SJ25-95-2566	2-1/2"	66'	250	125
SJ25-95-25100	2-1/2"	100'	250	125
SJ25-95-30100	3"	100'	250	125
SJ25-95-40100	4"	100'	250	125
SJ25-95-60100	6"	100'	250	125

This is a heavy duty, rubber lined, single jacket mill hose. Mill hose is a basic grade hose that has a variety of uses. It is primarily used for water movement, open end discharge, or low to medium pressure applications; used on location in industrial plants and construction sites where abrasion resistance is a factor. It is constructed using abrasion resistant staple yarns.

Tube: EPDM, Black.

Cover: White staple yarns.

Lengths: Standard in 50, 66 and 100 ft., also cut and/or coupled to clients individual requirements.

Couplings: Available in Brass or Aluminum. Please specify thread and/or coupling required NST, IPT, Storz, Nakajima, John Morris, etc..