1	Fire Hose (Section VII)		4
<u>Part No.</u>	<u>Description</u> <u>Pa</u>	age No.	
	Polyester UL, Red Nitrile Fire Hose and Mill Hose	5-8	
SJ4-92	Single Jacket UL Label, 400 PSI Fire Hose	5	
SJ5-92	Single Jacket UL Label in 500 PSI with Rocker-Lug coupling	gs 5	
SJ3-92	Single Jacket UL Label in 300 PSI with Pin-Lug couplings	5	
DJ6-92	Double Jacket UL Label, 600 PSI Fire Hose	6	
SJ25-95	Single Jacket, 250 PSI Mill Hose	7	
RC500SJ	Single Jacket, 500 PSI Rubber Fire Hose	8	
	Coast Guard Approved Nozzles	9	
AKRON-2032	1-1/2" Coast Guard Nozzle with FOG Head, CG-15	9	
AKRON-2046	2-1/2" Coast Guard Nozzle with FOG Head, CG-25	9	
AKRON-2415	1-1/2" x 4" Coast Guard Applicator with 1034 FOG Head	9	
AKRON-2015	1-1/2" x 10" Coast Guard Applicator with 1034 FOG Head	9	
AKRON-2225	2-1/2" x (6', 10', 12') Coast Guard Applicator, 1034 FOG He	ad 9	
AKRON-2033	1-1/2" FOG Tip with Chain for CG-15	9	
AKRON-2047	2-1/2" FOG Tip with Chain for CG-25	9	
AKRON-3020	Coast Guard Nozzle, 1-1/2" F NST Inlet with Pistol Grip	9	
AKRON-3022	Coast Guard Nozzle, 1-1/2" F NST Inlet	9	
AKRON-3025	Coast Guard Nozzle, 2-1/2" F NST Inlet	9	
	Brass Marine Nozzles & Industrial Fittings/Accessories	10-12	
565	Brass Shut Off - Straight Stream - FOG Nozzle	10	
572NB	Plain Hose Nozzle	10	
520-NIF	Industrial FOG Nozzle	11	
AKRON-3xxx	Portable By-Pass Eductors	11	
AKRON-1088	Piercing Applicator	11	
AKRON-2xxx	Industrial/Marine In-Line Eductors	11	
7233FNPG	Foam Tube with Pistol Grip	12	
7233FN	Foam Tube	12	
AKRON-3xxx	Akron Foam Nozzle with Pick-Up Tube	12	
AKRON-3xxx	Akron Foam Nozzle	12	
AKRON-39 to 42	Akron Tool Brackets	12	
	International Couplings and Fire Hose Nozzles	13-14	
7223-B	John Morris/British Instantaneous Firehose Coupling	13	
7223-N	Nakajima Firehose Coupling	13	
7223-S	Storz Firehose Coupling	13	
7223-M	Machino Firehose Coupling	13	
7223-1	Italian Firehose Coupling	13	
_	Page 1 of 4		
www	v.accordintl.com • Ph. (713) 641-2288 • Fax (713) 641-3636 -		
PAGE # 1		<i>l</i> lain	

	Fire Hose (Section VII) - <i>continued</i>	
<u>Part No.</u>	Description P	age No.
	International Fire Hose Nozzles, Valves, Adapters, Gaskets	14-18
KIT-2000 to 2001	John Morris (British Instantaneous) Nozzle	14
KIT-2002 to 2004	Nakajima Nozzle	14
KIT-2005 to 2007	Storz Nozzle	14
KIT-2008 to 2009	NST Nozzle	14
KIT-2010 to 2012	Storz Nozzle	14
KIT-2020 to 2021	John Morris (British Instantaneous) Unifire Nozzle	15
KIT-2022 to 2024	Nakajima Nozzle Unifire Nozzle	15
KIT-2025 to 2027	Storz Nozzle Unifire Nozzle	15
KIT-2028 to 2029	NST Nozzle Unifire Nozzle	15
KIT-2030 to 2032	Machino Nozzle Unifire Nozzle	15
KIT-2040 to 2041	John Morris (British Instantaneous) Unifire Nozzle	16
KIT-2042 to 2044	Nakajima Nozzle Unifire Nozzle	16
KIT-2045 to 2047	Storz Nozzle Unifire Nozzle	16
KIT-2048 to 2059	NST Nozzle Unifire Nozzle	16
KIT-2050 to 2052	Machino Nozzle Unifire Nozzle	16
KIT-2060 to 2061	John Morris Three Position Fire Hose Nozzle with Handle	17
KIT-2062 to 2064	Nakajima Three Position Fire Hose Nozzle with Handle	17
KIT-2065 to 2067	Storz Three Position Fire Hose Nozzle with Handle	17
KIT-2068 to 2069	NST Three Position Fire Hose Nozzle with Handle	17
KIT-2070 to 2072	Machino Three Position Fire Hose Nozzle with Handle	17
KIT-2080 to 2081	John Morris Jet Nozzle	18
KIT-2082 to 2084	Nakajima Jet Nozzle	18
KIT-2085 to 2087	Storz Jet Nozzle	18
KIT-2088 to 2089	NST Jet Nozzle	18
KIT-2090 to 2092	Machino Jet Nozzle	18
	International Brass Angle Valve with JIS10K and DIN PN10	19
KIT-2200 to 2201	John Morris Brass Angle Valve JIS10K Flange	19
KIT-2202 to 2204	Nakajima Brass Angle Valve JIS10K Flange	19
KIT-2205 to 2207	Storz Brass Angle Valve JIS10K Flange	19
KIT-2208 to 2209	NST Brass Angle Valve JIS10K Flange	19
KIT-2210 to 2212	Machino Brass Angle Valve JIS10K Flange	19
KIT-2220 to 2221	John Morris Brass Angle Valve DIN PN10 Flange	19
KIT-2222 to 2224	Nakajima Brass Angle Valve DIN PN10 Flange	19
KIT-2225 to 2227	Storz Brass Angle Valve DIN PN10 Flange	19
KIT-2228 to 2229	NST Brass Angle Valve DIN PN10 Flange	19
KIT-2230 to 2232	Machino Brass Angle Valve DIN PN10 Flange	19
14/14/14	Page 2 of 4 A.accordintl.com • Ph. (713) 641-2288 • Fax (713) 641-3636	
vv vv vv		Main

	Fire Hose (Section VII) - <i>continued</i>	
<u>Part No.</u>	Description	<u>Page No.</u>
	International Brass Globe Valve with JIS10K and DIN PN	10 20
KIT-2240 to 2241	John Morris Brass Globe Valve JIS10K Flange	20
KIT-2242 to 2244	Nakajima Brass Globe Valve JIS10K Flange	20
KIT-2245 to 2247	Storz Brass Globe Valve JIS10K Flange	20
KIT-2248 to 2249	NST Brass Globe Valve JIS10K Flange	20
KIT-2250 to 2252	Machino Brass Globe Valve JIS10K Flange	20
KIT-2260 to 2261	John Morris Brass Globe Valve DIN PN10 Flange	20
KIT-2262 to 2264	Nakajima Brass Globe Valve DIN PN10 Flange	20
KIT-2265 to 2267	Storz Brass Globe Valve DIN PN10 Flange	20
KIT-2268 to 2269	NST Brass Globe Valve DIN PN10 Flange	20
KIT-2270 to 2272	Machino Brass Globe Valve DIN PN10 Flange	20
	International Adapters, Hose Caps, Hose Plugs and Gask	kets 21-22
7233BF-xxMNST	Female John Morris x Male NST Adapter	21
7233BM-xxMNST	Male John Morris x Male NST Adapter	21
7233BF-xxFNST	Female John Morris x Female NST Adapter	21
7233NA-xxMNST	Nakajima x Male NST Adapter	21
7233NA-xxFNST	Nakajima x Female NST Adapter	21
7233SA-xxMNST	Storz x Male NST Adapter	21
7233SA-xxFNST	Storz x Female NST Adapter	21
7233B-xxxDC	John Morris Fire Hose Cap	22
7233N-xxxDC	Nakajima Fire Hose Cap	22
7233S-xxxDC	Storz Fire Hose Cap	22
7233I-xxxDP	Italian Fire Hose Plug	22
JM-150-G	John Morris Gasket	22
MA-150-G	Machino Gasket	22
NK-150-G	Nakajima Gasket	22
SZ-150-G	Storz Gasket	22
NST-150-G	NST Gasket	22
7233-DC	Cap for Fire Hose	22
-	Brass Marine, Industrial Fittings, and Spanner Wrenches	23-29
336-S	International Ship Connection	23
336-L	International Shore Connection	23
7233S-W	Storz Spanner Wrench	24
872-SW	Tabor Spanner Wrench	24
AHS	Adjustable Hook Spanner	24
876	Common Spanner Wrench	24
869	Combination Hook Spanner	24
	Page 3 of 4	

Main Main

	Fire Hose (Section VII) - <i>continued</i>	
Part No.	Description	Page No.
	(Spanner Wrenches Continued)	24
874	Universal Spanner Wrench	24
AKRON-446	Spanner Wrench Holder	24
879	Adjustable Hydrant Wrench	24
	Victor Pyrate Open End Wrench	24
	ANSI Fire Hose Valves, and Wyes	25-26
171U	Angle Valve	25
170U	Angle Valve	25
HAV	Angle Globe Valve	25
HGV	Angle Globe Valve	25
AKRON-2681	Brass Leader Line Wye	26
260	Plain Brass Wye	26
NRS-GV	Non-Rising Stem Gate Valve	26
2681-l	Import Brass Leader Line Wye	26
	ANSI Fire Adapters, Caps, and Plugs	27-29
363-M	Female x Male Brass Swivel Adapter	27
379	Double Female Brass Swivel Adapter (Pin-Lug and Rocke	er-Lug) 27
378	Double Male Adapter (Pin-Lug and Rocker-Lug)	27
359	Double Female Brass Hex Adapter	27
358	Double Male Hex Reducing/Increasing Nipple	28
369-P	Female x Male Brass Reducer (Pin-Lug and Rocker-Lug)	28
357	Female x Male Hex Reducing Nipple/Bushing	28
662-P	Brass Pin Lug Hose Cap with Chain	29
662-R	Brass Rocker Lug Hose Cap with Chain	29
661-R	Brass Rocker Lug Hose Plug with Chain	29
FHC	Fiberglass Cabinet for Fire Hose	30
406M	Pickhead Fire Axe with Wooden Handle	30
	Portable Handy Foam Unit	30

Page 4 of 4 www.accordintl.com • Ph. (713) 641-2288 • Fax (713) 641-3636

Main



No. SJ4-92 SINGLE JACKET UL LABEL 400 PSI FIRE HOSE



Part Number	Inside Diameter	Standard Length	Test Pressure -PSI	Service Pressure-PSI
SJ4-92-1550	1-1/2"	50'	400	200
SJ4-92-1575	1-1/2"	75'	400	200
SJ4-92-15100	1-1/2"	100'	400	200
SJ4-92-2550	2-1/2"	50'	400	200
SJ4-92-2575	2-1/2"	75'	400	200
SJ4-92-25100	2-1/2"	100'	400	200

This is a heavy duty, U.L. labeled, rubber lined, single jacket fire hose. The 100 percent polyester jacket offers excellent abrasion resistance for strength and durability. This fire hose is for use when ordinary rack and reel hose is not sufficient. This is the 400 pound test model which offers extra working pressure when necessary.

Tube: EPDM, Black

ъſ


Lengths: Standard in 50, 75 and 100 ft., also cut and/or coupled to clients individual requirements.

Couplings: Available in Brass or Aluminum. Please specify thread and/or coupling required NST, IPT, Storz, Nakajima, John Morris, etc..

* Note: Also available in 500 PSI Test Pressure, 250 Service Pressure and 300 PSI Test Pressure, 150 Service Pressure upon request. Please specify when ordering.

• www.accordintl.com • Ph. (713) 641-2288 • Fax (713) 641-3636

Main



No. DJ6-92 DOUBLE JACKET UL LABEL 600 PSI FIRE HOSE



Part Number	Inside Diameter	Standard Length	Test Pressure -PSI	Service Pressure-PSI
DJ6-92-1550	1-1/2"	50'	600	300
DJ6-92-1575	1-1/2"	75'	600	300
DJ6-92-15100	1-1/2"	100'	600	300
DJ6-92-2550	2-1/2"	50'	600	300
DJ6-92-2575	2-1/2"	75'	600	300
DJ6-92-25100	2-1/2"	100'	600	300

This is a heavy duty, U.L. labeled, rubber lined, double jacket fire hose. The 100 percent polyester jacket offers excellent abrasion resistance for strength and durability. This fire hose is for use when ordinary rack and reel hose is not sufficient. This is the 600 pound test model which offers extra working pressure when necessary.

Tube: EPDM, Black

ъſ


Lengths: Standard in 50, 75 and 100 ft. Cut and/or couple to clients individual requirements.

Couplings: Available in Brass or Aluminum. Please specify thread and/or coupling required NST, IPT, Storz, Nakajima, John Morris, etc..

* Note: An 800 PSI test pressure with 400 PSI service pressure is available upon request. Please specify when ordering.

• www.accordintl.com • Ph. (713) 641-2288 • Fax (713) 641-3636

Main



No. SJ25-95 SINGLE JACKET 250 PSI MILL HOSE



Part Number	Inside Diameter	Standard Length	Test Pressure -PSI	Service Pressure-PSI
SJ25-95-1550	1-1/2"	50'	250	125
SJ25-95-1566	1-1/2"	66'	250	125
SJ25-95-15100	1-1/2"	100'	250	125
SJ25-95-2050	2"	50'	250	125
SJ25-95-2066	2"	66'	250	125
SJ25-95-20100	2"	100'	250	125
SJ25-95-2550	2-1/2"	50'	250	125
SJ25-95-2566	2-1/2"	66'	250	125
SJ25-95-25100	2-1/2"	100'	250	125
SJ25-95-30100	3"	100'	250	125
SJ25-95-40100	4"	100'	250	125
SJ25-95-60100	6"	100'	250	125

This is a heavy duty, rubber lined, single jacket mill hose. Mill hose is a basic grade hose that has a variety of uses. It is primarily used for water movement, open end discharge, or low to medium pressure applications; used on location in industrial plants and construction sites where abrasion resistance is a factor. It is constructed using abrasion resistant staple yarns.

Tube: EPDM, Black.

ъſ

Cover: White staple yarns.

Lengths: Standard in 50, 66 and 100 ft., also cut and/or coupled to clients individual requirements.

Couplings: Available in Brass or Aluminum. Please specify thread and/or coupling required NST, IPT, Storz, Nakajima, John Morris, etc..

- www.accordintl.com • Ph. (713) 641-2288 • Fax (713) 641-3636

Main



Part Number	Inside Diameter	Standard Length	Test Pressure -PSI	Service Pressure-PSI
RC500SJ-1550	1-1/2"	50'	500	250
RC500SJ-1575	1-1/2"	75'	500	250
RC500SJ-15100	1-1/2"	100'	500	250
RC500SJ-2050	2"	50'	500	250
RC500SJ-2075	2"	75'	500	250
RC500SJ-20100	2"	100'	500	250
RC500SJ-2550	2-1/2"	50'	500	250
RC500SJ-2575	2-1/2"	75'	500	250
RC500SJ-25100	2-1/2"	100'	500	250

Nitrile synthetic rubber provides a rugged cover for this lightweight single jacket hose designed for use in industrial and marine environments. The deep ribbed pattern offers excellent abrasion resistance and the homogeneous heavy-duty one-piece cover and liner construction resists heat and most chemicals.

FEATURES: Nitrile synthetic rubber one-piece cover and liner, no drying required, abrasion resistant cover, impervious to water, oil, gas and most chemicals, heat resistant (welding sparks, etc.), virtually kink resistant, meets Underwriters and Factory Mutual standards, lightweight easy to handle

Tube/Cover: Red Nitrile.

Lengths: Standard in 50, 75 and 100 ft., also cut and/or coupled to clients individual requirements.

Couplings: Available uncoupled and coupled in Brass or Aluminum. Please specify thread and/or coupling required NST, IPT, Storz, Nakajima, John Morris, etc..

- www.accordintl.com • Ph. (713) 641-2288 • Fax (713) 641-3636

_____P

Main

COAST GUARD APPROVED NOZZLES

Coast Guard Nozzles with FOG Heads

ъſ



Coast Guard Applicators with FOG Heads



No. AKRON-2415 - 1-1/2" x 4" stainless steel tubing with 90° bend, includes style 1034 fog head.

No. AKRON-2015 - $1-1/2^{\circ}$ x 10° stainless steel tubing with 90° bend, includes style 1034 fog head.

No. AKRON-2225 (-6, -10, -12) - 2-1/2" x stainless steel tubing with 90° bend, includes style 1048 fog head. Available in 6', 10', and 12'.

Coast Guard Shipboard Vari-Nozzle with Pistol Grip



No. AKRON-3020 - Coast Guard Nozzle, 1-1/2" F NST inlet; Approval No. 162.027/15/0. A combination fog and straight stream nozzle designed for more efficiency with AFFF or water on-board ships. Brass construction, molded teeth, rubber like bumper and handle, constant gallonage in all FOG and straight stream patterns, flush without shutting down, 95 GPM. **No. AKRON-2032 - Coast Guard Nozzle, CG-15** 1-1/2" F NST inlet; Approval No. 162.027/9/0 for nozzle and Akron 2415 and 2015 applicator, includes Akron 2033 fog tip and chain. Fog flow - 55 GPM at 100 PSI.

No. AKRON-2046 - Coast Guard Nozzle, CG-25 2-1/2" F NST inlet; Approval No. 162.027/10/0 for nozzle and Akron 2225 applicator, includes Akron 2047 fog tip and chain. Fog flow - 106 GPM at 100 PSI.



Coast Guard FOG Tips



AKRON-2033 - 1-1/2" fog tip with chain for CG-15. **AKRON-2047** - 2-1/2" fog tip with chain for CG-25.

Coast Guard Shipboard Vari-Nozzle



No. AKRON-3022 - Coast Guard Nozzle, 1-1/2" F NST inlet; Approval No. 162.027/16/0. A combination fog and straight stream nozzle designed for more efficiency with AFFF or water on-board ships. 95 GPM.

No. AKRON-3025 - 2-1/2" F NST inlet; combination fog and straight stream nozzle designed for more efficiency with AFFF or water on offshore rigs and industrial applications . 250 GPM.

Main

- www.accordintl.com • Ph. (713) 641-2288 • Fax (713) 641-3636

No. 565 - Shut Off - Straight Stream - FOG Nozzle

This satin brass 1-1/2" size is highly recommended for use with interior fire protection equipment. Fire protection engineers and insurance companies recommend the use of the 1 1/2" 565 fog nozzle because of its effectiveness on fire, keeps water damage to a minimum. If the required nozzle shall be Underwriters' Listed approved and Factory Mutual Listed: for "A" & "B" Fires, please specify when ordering. Nozzles are also available in red thermoplastic (PN: 565P).




Part Number	Size	90° Spray GPM @ 100 PSI	Available Thread Types
565-075	3/4"		GHT, NST
565-100	1"	36	NPSH, NST
565-150	1-1/2"	85	NPSH, NST
565-200	2"	108	NPSH
565-250	2-1/2"	205	NPSH, NST

No. 572NB - Plain Hose Nozzle

For use on fire hose racks and reels and for other industrial applications where shut off valves are not required at the nozzle. Please specify thread type when ordering.

1-1/2" NPSH & NST nozzles are also available in red thermoplastic (PN: 572NBP)



www.accordintl.com • Ph. (713) 641-2288 • Fax (713) 641-3636

Main

ъſ

BRASS MARINE & INDUSTRIAL FITTINGS No. 520-NIF - Industrial FOG Nozzle

Heavy duty, low cost, fog nozzle, especially recommended for those locations where frequent service demands quality. Water flow can be quickly changed from, straight stream - to fog - to shut-off with a flick the wrist. Large rubber bumper protects the outer perimeter of nozzle tip and also provides a firm gripping surface. Specially designed to give uniform flow in all positions. **Not UL Listed or FM approved.**



ъſ

Part Number	Size & Thread
520-NIF-150NPSH	1-1/2" NPSH
520-NIF-150NST	1-1/2" NST

No. AKRON-3xxx - Portable By-Pass Eductor

These eductors have a built-in by-pass chamber allowing the operator to change from water to foam without shutting down.



Part Number	Inlet Size & Thread	Outlet Size & Thread	Flow (GPM)
AKRON-3062	1-1/2", 2-1/2" F NST	1-1/2" M NST	60
AKRON-3097	1-1/2", 2-1/2" F NST	1-1/2" M NST	95
AKRON-3127	1-1/2", 2-1/2" F NST	1-1/2" M NST	125

No. AKRON-2xxx - Industrial/Marine In-Line Eductor

These eductors have a built-in by-pass chamber allowing the operator to change from water to foam without shutting down.




Part Number	Inlet Size & Thread	Outlet Size & Thread	Flow (GPM)
AKRON-2328	1-1/2" F NST	1-1/2" M NST	90
AKRON-2900	1-1/2" F NST	1-1/2" M NST	90
AKRON-2901	1-1/2" F NST	1-1/2" M NST	90
AKRON-2325	1-1/2" F NST	1-1/2" M NST	95
AKRON-2120	2-1/2" F NST	2-1/2" M NST	120
-			

www.accordintl.com • Ph. (713) 641-2288 • Fax (713) 641-3636

No. AKRON-1088 - Piercing Applicator

Use a sledge hammer to drive the piercing applicator through concrete block, etc.. Designed to get water or foam to hidden trouble spots. Driving button and point made of hardened tool steel. Impinging jets for a more dense fog pattern. Compatible with Class A and B foams. 1-1/2" F NST swivel inlet. Specify 3' or 6' lengths when ordering. Flow rate of 125 GPM.

Main



Akron Foam Nozzles (Available with & without Pick-Up Tube)

Combination Akrolite and Pyrolite, units with pickup tube preset for 6%, can be changed to 1/2%, 1% or 3%. Expansion rate up to 14:1.

E)				
Part Number	Inlet Size & Thread	Flow (GPM)	Part Number	Inlet Size & Thread	Flow (GPM)
AKRON-3601	1-1/2" F NST	60	AKRON-3602	1-1/2" F NST	60
AKRON-3951	1-1/2" F NST	95	AKRON-3952	1-1/2" F NST	95
AKRON-3121	2-1/2" F NST	120	AKRON-3120	2-1/2" F NST	120

Akron Tool Brackets

These heavy duty tool brackets with covered jaws for securing various tools. Style 39 and 40 are for smaller tools and applicators with 3/4" to 1" OD. Style 40 and 42 are for 1-1/2" and 2-1/2" applicators and other tools, such as axe handles. Akrolite construction.





Main

Part Number	Size	Part Number	Size
AKRON-39	3/4" to 1" Horizontal	AKRON-41	3/4" to 1" Vertical
AKRON-40	1-1/2" to 2-1/2" Horizontal	AKRON-42	1-1/2" to 2-1/2" Vertical

www.accordintl.com • Ph. (713) 641-2288 • Fax (713) 641-3636

INTERNATIONAL BRASS MARINE FIRE HOSE COUPLINGS

PART#: 7233B - John Morris/British instantaneous Firehose Coupling

Conform to BS 336 British Standard design. The distinctive arms on the female coupling are spring-loaded and lock onto the male fitting when pushed together. Pulling the arms away from the coupling releases the fittings.



ъſ

Part Number	Hose ID Size	Female Size	Male Size	IMPA Code
7233B-150	1-1/2"	1-1/2"	1-1/2"	330859
7233B-200	2"	2-1/2"	2-1/2"	330860
7233B-250	2-1/2"	2-1/2"	2-1/2"	330861

PART #: 7233N - Nakajima Firehose Coupling

Conform to JIS 7335 standard. The two halves are identical and a quarter turn locks the couplings together.



Part Number	Hose ID Size	Coupling Size	IMPA Code
7233N-150	1-1/2"	1-1/2"	330851
7233N-200	2"	2"	330852
7233N-250	2-1/2"	2-1/2"	330853
7233N-2515	1-1/2"	2-1/2"	330891

PART #: 7233S - Storz Firehose Coupling

Conform to the German standard DIN 14302 and DIN 14303. A quarter turn mates the two identical halves.





Part Number	Hose ID Size	Coupling Size	IMPA Code
7233S-150	1-1/2"	1-1/2"	
7233S-200	2"	2"	330875
7233S-250	2-1/2"	2-1/2"	

PART #: 7233M - Machino Firehose Coupling

Conform to JIS B9911. These are push-to-connect coupling with a distinctive outer rubber bumper on the female half. Pushing the flange on the male half releases the fittings.



Part Number	Hose ID Size	Female Size	Male Size	IMPA Code
7233M-150	1-1/2"	1-1/2"	1-1/2"	330855
7233M-200	2"	2"	2"	330856
7233M-250	2-1/2"	2-1/2"	2-1/2"	330857

PART #: 7233I - Italian Firehose Coupling



Part Number	Hose ID Size	Coupling Size
72331-45	1-3/4"	1-3/4"
72331-70	2-3/4"	2-3/4"

Main

www.accordintl.com • Ph. (713) 641-2288 • Fax (713) 641-3636

PN: KIT-2000 to KIT-2012; 3 Position Fire Hose Nozzle

Three position nozzles combine the features of straight stream and fog nozzles. The rubber bumper of the nozzle can be twisted from shut off position to a choice of straight stream or fog spray. Nozzles are available in the various sizes and coupling style shown. The coupling adapter is threaded into the nozzle body to permit interchanging male adapter.

John Morris (British Instantaneous) Nozzle



Ър

Kit Number	Size	Length
KIT-2000	1-1/2"	5-1/2"
KIT-2001	2-1/2"	7-1/4"



Nakajima Nozzle

Kit Number	Size	Length	IMPA Code
KIT-2002	1-1/2"	5"	330831
KIT-2003	2"	6-3/4"	330832
KIT-2004	2-1/2"	6-3/4"	330833



Kit Number	Size	Length
KIT-2005	1-1/2"	5-1/4"
KIT-2006	2"	6-3/4"
KIT-2007	2-1/2"	6-3/4"




NST Nozzle

Kit Number	Size	Length	IMPA Code
KIT-2008	1-1/2"	5"	330834
KIT-2009	2-1/2"	6-1/4"	330836

Machino Nozzle

Kit Number	Size	Length	IMPA Code
KIT-2010	1-1/2"	5-1/4"	330837
KIT-2011	2"	6-3/4"	330838
KIT-2012	2-1/2"	6-3/4"	330839



PN: KIT-2020 to KIT-2032; 3 Position Unifire Fire Hose Nozzle

Three position nozzles combine the features of straight stream and fog nozzles. The rubber bumper of the nozzle can be twisted from shut off position to a choice of straight stream or fog spray. Nozzles are available in the various sizes and coupling style shown. The coupling adapter is threaded into the nozzle body to permit interchanging male adapter to the midsection and to the nozzle.

John Morris (British Instantaneous) Nozzle

Nakajima Nozzle



Ъ

Kit Number	Size	Length
KIT-2020	1-1/2"	8-1/2"
KIT-2021	2-1/2"	10-1/2"



Kit Number	Size	Length	IMPA Code
KIT-2022	1-1/2"	8"	330831
KIT-2023	2"	10"	330832
KIT-2024	2-1/2"	10-1/4"	330833

Storz Nozzle



Kit Number	Size	Length
KIT-2025	1-1/2"	8-1/4"
KIT-2026	2"	10"
KIT-2027	2-1/2"	10-1/4"

NST Nozzle



Kit Number	Size	Length	IMPA Code
KIT-2028	1-1/2"	8"	330834
KIT-2029	2-1/2"	9-3/4"	330836

Machino Nozzle



Kit Number	Size	Length	IMPA Code
KIT-2030	1-1/2"	8-1/4"	330837
KIT-2031	2"	10"	330838
KIT-2032	2-1/2"	10-1/4"	330839

PAGE # 15

www.accordintl.com • Ph. (713) 641-2288 • Fax (713) 641-3636



PN: KIT-2040 to KIT-2052; 3 Position Unifire Fire Hose Nozzle

Three position nozzles combine the features of straight stream and fog nozzles. The rubber bumper of the nozzle can be twisted from shut off position to a choice of straight stream or fog spray. Nozzles are available in the various sizes and coupling style shown. The coupling adapter is threaded into the nozzle body to permit interchanging male adapter.

John Morris (British Instantaneous) Nozzle



Ъ

Kit Number	Size	Length
KIT-2040	1-1/2"	11-1/2"
KIT-2041	2-1/2"	14-1/4"

Nakajima Nozzle

	Kit Number	Size	Length	IMPA Code
	KIT-2042	1-1/2"	11"	330831
The second distance of	KIT-2043	2"	13-1/4"	330832
	KIT-2044	2-1/2"	13-3/4"	330833

Storz Nozzle



Kit Number	Size	Length
KIT-2045	1-1/2"	11-1/4"
KIT-2046	2"	13-1/4"
KIT-2047	2-1/2"	13-3/4"

Main

NST Nozzle



Machino Nozzle

Kit Number	Size	Length	IMPA Code	
KIT-2050	1-1/2"	11-1/4"	330837	
KIT-2051	2"	13-1/4"	330838	
KIT-2052	2-1/2"	13-3/4"	330839	

www.accordintl.com • Ph. (713) 641-2288 • Fax (713) 641-3636

PN: KIT-2060 to KIT-2072; 2 Piece, Three Position Fire Hose Nozzle With Handle

Three position nozzles combine the features of straight stream and fog nozzles. The lever can be moved from a shut off position to a choice of straight stream or fog spray. When the lever is in the fog position, the spray is adjusted by twisting the heavy rubber bumper. Nozzles are available in various sizes and coupling a shown. The coupling adapter is threaded into the nozzle body to permit interchanging male adapter.



John Morris (British Instantaneous) Nozzle

Kit Number	Size	Length
KIT-2060	1-1/2"	8-1/4"
KIT-2061	2-1/2"	10-1/2"

Nakajima Nozzle

Kit Number	Size	Length	IMPA Code
KIT-2062	1-1/2"	7-3/4"	330831
KIT-2063	2"	8-1/2"	330832
KIT-2064	2-1/2"	10"	330833

Storz Nozzle

Kit Number	Size	Length
KIT-2065	1-1/2"	8"
KIT-2066	2"	9"
KIT-2067	2-1/2"	10"

NST Nozzle

Kit Number	it Number Size Leng		IMPA Code
KIT-2068	1-1/2"	7-3/4"	330834
KIT-2069	2-1/2"	9-1/2"	330836

Machino Nozzle

Kit Number	Number Size Length		IMPA Code	
KIT-2070	1-1/2"	8"	330837	
KIT-2071	2"	8-1/2"	330838	
KIT-2072	2-1/2"	10"	330839	

www.accordintl.com • Ph. (713) 641-2288 • Fax (713) 641-3636


ъſ

Main

PN: KIT-2080 to KIT-2092; Jet Fire Hose Nozzle

Our brass jet stream nozzles are available with a variety of coupling designs. The tips are designed to provide a straight stream flow with tip diameters of 13mm for 1-1/2" nozzles, 15mm for 2" and 20mm for 2-1/2".

John Morris (British Instantaneous) Jet Nozzle





Nakajima Jet Nozzle

Kit Number	Size	Length	IMPA Code
KIT-2082	1-1/2"	10-1/4"	330801
KIT-2083	2"	11-3/4"	330803
KIT-2084	2-1/2"	12-1/4"	330804



Storz Jet Nozzle

Kit Number	Size Lengt	
KIT-2085	1-1/2"	10-1/2"
KIT-2086	2"	11-3/4"
KIT-2087	2-1/2"	13-1/4"

Main

NST Jet Nozzle

	ST IN THE OWNER					
	California and a subscription of the subscript	The survey of the survey of the survey of	Kit Number	Size	Length	IMPA Code
1			KIT-2088	1-1/2"	10"	330806
			KIT-2089	2-1/2"	12"	330808

	Machino Jet Nozzle				
and the second s	Kit Number	Size	Length	IMPA Code	
Summer summer and summer su	KIT-2090	1-1/2"	10-1/2"	330809	
	KIT-2091	2"	11-1/4"	330810	
	KIT-2092	2-1/2"	13-1/4"	330811	
www.accordintl.com • Ph. (713) 641-2288 • Fax (713) 641-3636					

PAGE # 18

Ъ

INTERNATIONAL BRASS MARINE FIRE HOSE VALVES

PN: KIT-2200 to KIT-2232; Brass Angle Valve with JIS10K or DIN PN 10 flange

Cast Brass Hose Angle Valve available in either JIS10K or DIN PN 10 flanged inlet with coupling adapter that is threaded into the valve body to permit interchanging the male adapter on the outlet. Rated for 16 Bar.

John Morris (British Instantaneous)

JIS10K Flange Valve			
Kit Number	Size		
KIT-2200	1-1/2" (40mm)		
KIT-2201	2-1/2" (65mm)		

DIN PN10 Flange Valve

Size

1-1/2" (40mm)

2-1/2" (65mm)

Kit Number

KIT-2220

KIT-2221

Ъ



 Storz

 Storz

 JIS10K Fange Valve

 Kit Number
 Size

 Kit7-2205
 1-1/2" (40mm)

 KIT-2206
 2" (50mm)

 KIT-2207
 2-1/2" (65mm)

DIN PN10 Flange Valve			
Kit Number Size			
KIT-2225	1-1/2" (40mm)		
KIT-2226	2" (50mm)		
KIT-2227	2-1/2" (65mm)		





JIS10K Flange Valve			
Kit Number	Size	IMPA Code	
KIT-2202	1-1/2" (40mm)	751714	
KIT-2203	2" (50mm)	751722	
KIT-2204	2-1/2" (65mm)	751723	

DIN PN10 Flange Valve		
Kit Number Size		
KIT-2222	1-1/2" (40mm)	
KIT-2223	2" (50mm)	
KIT-2224	2-1/2" (65mm)	



Machino

JIS10K Flange Valve		
Kit Number	Size	
KIT-2210	1-1/2" (40mm)	
KIT-2211	2" (50mm)	
KIT-2212	2-1/2" (65mm)	

DIN PN10 Flange Valve		
Size		
1-1/2" (40mm)		
2" (50mm)		
2-1/2" (65mm)		



JIS10K Flange Valve			
Kit Number	Size		
KIT-2208	1-1/2" (40mm)		
KIT-2209	2-1/2" (65mm)		

NST

Main

DIN PN10 Flange Valve	
Kit Number	Size
KIT-2228	1-1/2" (40mm)
KIT-2229	2-1/2" (65mm)

www.accordintl.com • Ph. (713) 641-2288 • Fax (713) 641-3636

INTERNATIONAL BRASS MARINE FIRE HOSE VALVES

PN: KIT-2240 to KIT-2272; Brass Globe Valve with JIS10K or DIN PN 10 flange

Cast Brass Hose Globe Valve available in either JIS10K or DIN PN 10 flanged inlet with coupling adapter that is threaded into the valve body to permit interchanging the male adapter on the outlet. Rated for 16 Bar.

John Morris (British Instantaneous)

Kit Number

KIT-2240

KIT-2241

Kit Number

KIT-2260

KIT-2261

JIS10K Flange Valve

DIN PN10 Flange Valve

Size

1-1/2" (40mm)

2-1/2" (65mm)

Size


1-1/2" (40mm)

2-1/2" (65mm)

Ъ

Storz

JIS10K Flange Valve	
Kit Number	Size
KIT-2245	1-1/2" (40mm)
KIT-2246	2" (50mm)
KIT-2247	2-1/2" (65mm)





NST

Nakajima

JIS10K Flange Valve		
Kit Number	Size	IMPA Code
KIT-2242	1-1/2" (40mm)	751712
KIT-2243	2" (50mm)	751717
KIT-2244	2-1/2" (65mm)	751718

DIN PN10 Flange Valve	
Kit Number	Size
KIT-2262	1-1/2" (40mm)
KIT-2263	2" (50mm)
KIT-2264	2-1/2" (65mm)

Machino

JIS10K Flange Valve	
Kit Number	Size
KIT-2250	1-1/2" (40mm)
KIT-2251	2" (50mm)
KIT-2252	2-1/2" (65mm)

DIN PN10 Flange Valve	
Size	
1-1/2" (40mm)	
2" (50mm)	
2-1/2" (65mm)	


Main




Kit Number	Size	
KIT-2248	1-1/2" (40mm)	
KIT-2249	2-1/2" (65mm)	
DIN PN10 Flange Valve		
Kit Number	Size	
KIT-2268	1-1/2" (40mm)	
KIT-2269	2-1/2" (65mm)	
	Z-1/Z (UJIIIII)	

JIS10K Flange Valve

www.accordintl.com • Ph. (713) 641-2288 • Fax (713) 641-3636





No. 336-S - International Ship Connection

336-S Ship connection is for use with 336-L Shore Connection. The International Ship Connection is a standard 2-1/2" 150 lb. ASA flange drilling. The flange has a 2-1/2" female fire hose thread (NST/NH) to match fire hose threads on the ship. The flange has 4 slots with Bolt Circle Diameter of 5-1/2", the Outside Diameter is 7". Flange is slotted rather than drilled so that it can be used with non standard flanges. Connection is supplied with bolts, nuts, washers, and gasket.

Ър



No. 336-BOX - International Ship/Shore Connection Storage Box. This PVC cabinet is rugged, watertight, corrosion resistant with a twist handle. The cabinet can store up to 2 pieces.

No. 336-L - International Shore Connection

336-L Shore connection is for use with 336-S Ship Connection. The International Shore Connection is a standard 2-1/2" 150 lb. ASA flange drilling. The flange has a 2-1/2" female fire hose thread (NST/NH) to match fire hose threads on the ship. The flange has 4 holes with Bolt Circle Diameter of 5-1/2", the Outside Diameter is 7". The International Shore Connection is supplied with bolts, nuts, washers, and gasket.

Main

www.accordintl.com • Ph. (713) 641-2288 • Fax (713) 641-3636

PAGE # 23

No. 874 - Universal Spanner Wrench

ъſ

Our most popular spanner available in Brass, Aluminum and plated Malleable Iron. Handle end has pry lever, gas cock shut-off, and door stop. Fits all lugs.



No. 872-SW - Tabor Spanner Wrench An adjustable malleable iron head designed to take all sizes of pentagon or square hydrant nuts. Spanner hook fits pin, rocker or navy slot lugs 3/4" to 4-1/2".



No. AHS - Adjustable Hook Spanner An adjustable hook spanner available in a variety of sizes, ranging from: 3/4" to 2", 1-1/4" to 3" and 2" to 4-3/4".



No. 876 - Common Spanner Wrench Used on pin lug type fittings, in sizes 1-1/2" through 4". Available in plated Malleable Iron and Brass.

No. 869 - Combination Hook Spanner

Designed to fit pin, rocker lug, and slotted couplings and adapters from 3/4" to 3" The handle angle is designed for sure grip "in the hand" and "on the coupling".



No. 7233S-W - Storz Spanner Wrench Spanner wrench for Storz firehose couplings 1-1/2" through 2-1/2".



No. AKRON-446 - Spanner Wrench Holder

Aluminum dual wrench holder designed so wrenches can be snatched loose or replaced with one hand.



No. 879 - Adjustable Hydrant Wrench

879 has an adjustable malleable iron head designed to take all sizes of pentagon or square hydrant nuts. Spanner hook fits pin, rocker or navy lugs 3/4" to 4-1/2".



No. 171U - Angle Valve

ъſ

Part 171U is a double female angle valve, cast brass body, satin trim complete with red enamel steel handle. Hydraulically tested in open and closed position to twice its rated pressure. If Underwriters' Listed is required, please specify when ordering.



Part	Size with
Number	Thread Type
171U-150	1-1/2" F NPT x 1-1/2" F NPT
171U-250	2-1/2" F NPT x 2-1/2" F NPT

No. 170U - Angle Valve

Part 170U is a female and male Underwriters' Listed angle valve, cast brass body, satin trim complete with red enamel steel handle. Hydraulically tested in open and closed position to twice its rated pressure. If Underwriters' Listed is required, please specify when ordering.



Part Number	Size with Thread Type
170U-150	1-1/2" F NPT x 1-1/2" M NST
170U-150-NPSH	1-1/2" F NPT x 1-1/2" M NPSH
170U-250	2-1/2" F NPT x 2-1/2" M NST
170U-250-NPSH	2-1/2" F NPT x 2-1/2" M NPSH

No. HAV - Angle Globe Valve

Cast brass angle globe valve, with ASA 150# flanged inlet x male fire hose thread outlet with cap and chain.



Part Number	Flange Size x Thread Type
HAV-150NST	1-1/2" 150# x 1-1/2" M NST
HAV-250NST	2-1/2" 150# x 2-1/2" M NST

No. HGV - Globe Valve

Cast brass straight globe valve, with ASA 150# flanged inlet x male fire hose thread outlet with cap and chain.



Part Number	Flange Size x Thread Type	
HGV-150NST	1-1/2" 150# x 1-1/2" M NST	
HGV-250NST	2-1/2" 150# x 2-1/2" M NST	

Main



No. 363-M - Female x Male Brass Swivel Adapter

ф



Part Number	Size & Threads	
363-M-02	1-1/2" F NST x 1-1/2" M NPT	
363-M-03	1-1/2" F NPSH x 1-1/2" M NPT	
363-M-53	2-1/2" F NST x 1-1/2" M NPT	
363-M-04	2-1/2" F NST x 1-1/2" M NST	
363-M-05	2-1/2" F NST x 2" M NPT	
363-M-07	2-1/2" F NST x 2-1/2" M NPT	
363-M-08	2-1/2" F NST x 3" M NPT	

No. 379 - Double Female Brass Swivel Adapter (available in Pin-Lug and Rocker-Lug) 

Part Number	Size & Threads	
379-P-02	1-1/2" F NST x 1-1/2" F NST	
379-P-52	1-1/2" F NPT x 1-1/2" F NST	
379-P-03	1-1/2" F NPSH x 1-1/2" F NST	
379-P-53	1-1/2" F NPT x 1-1/2" F NPSH	
379-P-54	1-1/2" F NPSH x 2-1/2" F NPSH	
379-P-06	2-1/2" F NST x 2-1/2" F NST	
379-P-1525	2-1/2" F NST x 1-1/2" F NPT	
379-P-56	2-1/2" F NPSH x 2-1/2" F NPSH	
379-P-65	2-1/2" F NST x 2" F NPT	
379-P-66	2-1/2" F NPT x 2-1/2" F NST	
379-P-2530	2-1/2" F NST x 3" F NPT	
379-P-30	3" F NST x 3" F NPT	

No. 378 - Double Male Adapter (available in Pin-Lug, Rocker-Lug & Slotted)



Part Number	Size & Threads		
378-1515-54	1-1/2" M NPSH x 1-1/2" M NPSH		
378-1515-57	1-1/2" M NST x 1-1/2" M NST		
378-2525-03	2-1/2" M NPSH x 2-1/2" M NST		
378-2525-54	2-1/2" M NPSH x 2-1/2" M NPSH		
378-2525-56	2-1/2" M NPSH x 2-1/2" M NPT		
378-2525-57	2-1/2" M NST x 2-1/2" M NST		

No. 359 - Double Female Brass Hex Adapter



Part Number	Size & Threads
359-150NST	1-1/2" F NST x 1-1/2" F NST
359-150SP	1-1/2" F NST x 1-1/2" F NPT
359-250NST	2-1/2" F NST x 2-1/2" F NST
359-250SP	2-1/2" F NST x 2-1/2" F NPT

Main

- www.accordintl.com • Ph. (713) 641-2288 • Fax (713) 641-3636 •

No. 358 - Double Male Hex **Reducing/Increasing Nipple**

ф



Part Number	Size & Threads		
358-7515-52	3/4" M NPT x 1-1/2" M NST		
358-1010-03	1" M NPT x 1" M NPSH		
358-1515-52	1-1/2" M NPT x 1-1/2" M NST		
358-1515-02	1-1/2" M NST x 1-1/2" M NST		
358-1515-03	1-1/2" M NPT x 1-1/2" M NPSH		
358-1520-56	1-1/2" M NST x 2" M NPT		
358-2515-53	2-1/2" M NPT x 1-1/2" M NST		
358-2515-04	2-1/2" M NST x 1-1/2" M NPT		
358-2515-05	2-1/2" M NST x 1-1/2" M NST		
358-2520-56	2-1/2" M NST x 2" M NPT		
358-2525-37	2-1/2" M NST x 2-1/2" M NPT		
358-2525-47	2-1/2" M NPSH x 2" M NPT		
358-2525-57	2-1/2" M NST x 2-1/2" M NST		
358-3025-28	3" M NPT x 2-1/2" M NST		
358-3030-29	3" M NPT x 3" M NST		
358-4025-40	4" M NPT x 2-1/2" M NST		

No. 369-P - Female x Male Brass Reducer (available in Pin & Rocker Lug)



Part Number	Size & Threads		
369P-1510-94	1-1/2" F NST x 1" M NST		
369P-1515-04	1-1/2" F NST x 1-1/2" F NST		
369P-1515-43	1-1/2" F NST x 1-1/2" M NPSH		
369P-1515-44	1-1/2" F NST x 1-1/2" M NPT		
369P-1515-77	1-1/2" F NPSH x 1-1/2" M NST		
369P-2015-45	2" F NPT x 1-1/2" M NST		
369P-2575-63	2-1/2" F NST x 3/4" M NPT		
369P-2575-73	2-1/2" F NST x 3/4" M GHT		
369P-2510-93	2-1/2" F NST x 1" M NPSH		
369P-2515-45	2-1/2" F NPT x 1-1/2" M NST		
369P-2515-55	2-1/2" F NST x 1-1/2" M NPT		
369P-2515-65	2-1/2" F NST x 1-1/2" M NPSH		
369P-2515-75	2-1/2" F NST x 1-1/2" M NST		
369P-2520-06	2-1/2" NST x 2" M NPT		
369P-2520-26	2-1/2" F NST x 2" M NPSH		
369P-2520-76	2-1/2" F NPSH x 2 M NPT		
369P-3025-17	3" F NPT x 2-1/2" M NST		



No. 357 - Female x Male Hex **Reducing Nipple/Bushing**



Part Number	Size & Threads	
357-7510-81	3/4" F GHT x 1" M NPT	
357-1075-02	1" F NPT x 3/4" M GHT	
357-1010-02	1" F NPT x 1" M NPSH	
357-1510-05	1-1/2" F NPT x 1" M NPT	
357-1510-32	1-1/2" F NST x 1" M NPT	
357-1515-01	1-1/2" F NPSH x 1-1/2" M NST	
357-1515-03	1-1/2" F NPSH x 1-1/2" M NPSH	
357-1515-04	1-1/2" F NST x 1-1/2" M NST	
357-1515-25	1-1/2" F BSP x 1-1/2" MNST	
357-1515-52	1-1/2" F NPT x 1-1/2" M NST	
357-1515-53	1-1/2" F NST x 1-1/2" M NPT	
357-1525-42	1-1/2" F NPT x 2-1/2" M NST	
357-1525-55	1-1/2" F NST x 2-1/2" M NST	

Part Number	Size & Threads	
357-2025-08	2" F NPT x 2-1/2" M NST	
357-2575-63	2-1/2" F NST x 3/4" M NPT	
357-2515-04	2-1/2" F NPT x 1-1/2" M NST	
357-2515-54	2-1/2" F NST x 1-1/2" M NST	
357-2520-84	2-1/2" F NST x 2" M NPT	
357-2525-04	2-1/2" F NST x 2-1/2" M NST	
357-2525-05	2-1/2" F NPSH x 2-1/2" M NPT	
357-2525-06	2-1/2" F NST x 2-1/2" M NPT	
357-2525-07	2-1/2" F NPT x 2-1/2" M NST	
357-2525-08	2-1/2" F NPSH x 2-1/2" M NST	
357-2525-25	2-1/2" F BSP x 2-1/2" MNST	
357-3025-17	3" F NPT x 2-1/2" M NST	
357-4025-09	4" F NST x 2-1/2" M NST	
357-4025-17	4" F NPT x 2-1/2" M NST	

- www.accordintl.com • Ph. (713) 641-2288 • Fax (713) 641-3636 -Main

No. 662-P - Brass Pin Lug No. 662-SL - Brass Slotted No. 662-R - Brass Rocker Lug Hose Cap with Chain Hose Cap with Chain Hose Cap with Chain Part Number Thread Lug Size Note: (P = Pin-Lug) Туре **Types** 3/4" 662-P-075 GHT Pin, Hex 1" 662-P-100-NPSH NPSH Pin 1" 662-P-100 NST Pin, Hex NPSH Pin 662-P-125 1-1/4" 662-P-150-NPSH 1-1/2" NPSH Pin 662-P-150 1-1/2" Pin, Rocker NST 662-P-250-NPSH 2-1/2" NPSH Pin Pin, Rocker, Slotted 662-P-250 2-1/2" NST 3" NPSH Pin 662-P-300-NPSH 662-P-300 3" NST Pin 662-P-400-NPSH 4" NPSH Pin, Rocker 4" 662-P-400 NST Pin

Hose caps are also available in Aluminum and Thermoplastic.

No. 661-P - Brass Pin Lug Hose Plug with Chain (Shown is Rocker Lug)



Part Number Note: (P = Pin-Lug)	Size	Thread Type	Lug Types
661-P-150-NPSH	1-1/2"	NPSH	Pin
661-P-250	2-1/2"	NST	Pin, Rocker
661-P-250-NPSH	2-1/2"	NPSH	Pin
661-P-250	1-1/4"	NST	Pin, Rocker
661-P-400AL (Alum only)	4"	NST	Pin


Hose plugs are also available in Aluminum.

www.accordintl.com • Ph. (713) 641-2288 • Fax (713) 641-3636 •

Ъ

____.

Main



PORTABLE HANDY FOAM UNIT

The "HANDY FOAM" unit brings you everything you need in one package for your portable foam application. The latest in foam making with our exclusive self-educting foam nozzle and removable metering device that eliminates the use of eductors that have exceptionally high pressure drop.

The "HANDY FOAM" has NO pressure drop, meaning you can work at lower pressure from 30 to 600 PSI and always accomplish a better reach and expansion ratio than with anything else you have used.

The shutoff ball is machined out of high-grade aluminum alloy with 50 microns of PTFE impregnated which provides years of smooth action with minimal wear.


Unit comes complete with: 2.5 gallon reservoir, self-educting nozzle, low and medium foam attachments 20 GPM, mounting bracket, shoulder strap, metering orifices 0.4 %, 1 %, 3 % et 6 %.

- Compact and lightweight
- Ergonomic design for maximum comfort
- Superior reach and penetration
- Engineered to be extremely user friendly
- High impact polyethylene reservoir of 2.5 gallon / 10 liter
- Low & Medium self-educting attachments for the nozzle
- Carrying shoulder straps
- 20 GPM standard
- 0.4%, 1%, 3% and 6% metering orifices

Complete Unit Dimensions: 19.4" L x 6.1" W x 21.5" H; 20 lbs. Low expansion nozzle: 20.1" x 3.1" x9.1"; 3.3 lbs. Medium expansion nozzle: 18.5" x 5.4" x 9.1"; 6.2 lbs.

Optional accessories include:

- Metering orfice
- Piercing nozzle
- Turbine tip
- Back-Pak



Main